

# EB-6 PLUS™ Transceiver

HIGH SPEED IP/ETHERNET DATALINK



Intuicom's EB-6 PLUS is a long-range, high-speed industrial wireless transceiver enabling both IP and serial connectivity. The EB-6 PLUS provides remote serial and IP data connectivity to IP based networks, enabling high performance data transport, positioning and access for fixed or mobile operations.

## FUNCTIONALITY AND FLEXIBILITY

Providing Ethernet and dual serial port connectivity simultaneously, the EB-6 PLUS offers a single solution to a broad range of applications. With up to 867 Kbps of available bandwidth, the EB-6 PLUS is flexible enough to support legacy serials as well as the most current IP devices. Consistent with Intuicom's other transceivers, the EB-6 PLUS is multi-functional and may be operated as the access point, end-point, repeater, or endpoint/repeater in point-to-point and point-to-multipoint communications.

## "BEST-IN-CLASS" RF PERFORMANCE

Employing Intuicom's robust and secure frequency hopping spread spectrum technology, the EB-6 PLUS is inherently resistant to interference from other RF equipment including other spread spectrum radios. Empowered with an ultra sensitive and highly selective RF receiver, the EB-6 PLUS provides real-time, robust data transport. With top performance and security that includes 128-bit AES encryption, the EB-6 PLUS provides superior "real world" throughput and performance over other wireless products.

## EASE OF USE

Intuicom's embedded web-based set-up makes getting up and running a straight-forward and simple process. Not only is the EB-6 PLUS easy to set-up, but Intuicom makes it simple to optimize the performance of each transceiver on the network after it has been installed in the field. An IP addressable embedded server hosts a dynamic web page that provides diagnostics, performance criteria and access to key parameters for on-demand remote configuration.

With proven performance in dense RF environments, Intuicom's wireless networks power through the congestion to provide reliable data transport where other technologies fall short.

*To learn more about enabling wireless networking for your applications, please contact us at: [info@intuicom.com](mailto:info@intuicom.com) or call (303) 449-4330*

## KEY FEATURES

- Ethernet and dual serial port interfaces
- 40+ mile range (LOS)
- Secure, license-free 902-928 MHz FHSS technology
- Single Unit Operation™: any unit may serve as an access point, end point or repeater
- 867 Kbps over the air data rates
- 128-bit AES Encryption
- RADIUS compliant authentication
- Low power consumption
- Auto-crossover switching
- Optional embedded GPS

## APPLICATIONS

- Traffic system controls
- Video surveillance
- Security systems
- High speed backbones
- Mobile data & remote access
- Remote asset management
- AVL/Vehicle tracking
- Remote sensor data collection



# EB-6 PLUS™ Transceiver

HIGH SPEED IP/ETHERNET DATALINK

## GENERAL SPECIFICATIONS

Enclosure	Ruggedized extruded aluminum
Size	H: 56.6 mm x W: 74.4 mm x L: 165.1 mm
Weight	427 g
Operating Temperature	-40° C to +75° C
Connectors	
External Antenna	TNC-F
Data Interface	Ethernet: 10/100 BaseT, RJ45 (auto crossover) COM1: RS232/422/485, DB9-F COM2: RS232/422/485, DB9-F
Power (@ 12 VDC)	< 140 mA Receive; < 550 mA Transmit; 71 mA Idle
Input Voltage	6-30 VDC
Operating Modes	
Network Configurations	Point-to-Point, Point-to-Multipoint
Unit Operating Modes	Access Point, Repeater, End Point, Repeater/End Point
Unit Configurations	Access Point (Ethernet and/or serial), End Point (Ethernet and/or serial)

## WIRELESS TRANSCEIVER

Frequency Range	902 - 928 MHz (FHSS/FCC DTS)
Transmitter	
Output Power	5 mW to 1 W; Programmable
Range, Line of Sight	40 Miles / 15 Miles dependent on configuration
Modulation	2-level GFSK
Occupied Bandwidth	611.2 KHz
Spreading Method	Frequency Hopping/FCC DTS
Hopping Patterns	15 per band, 105 total, user selectable
Hopping Channels	41
Frequency Zones	16 Zones, 2-3 Channels per Zone
Receiver	
Sensitivity	-102 dBm at 10 <sup>-6</sup> BER at 614 Kbps -100 dBm at 10 <sup>-6</sup> BER at 867 Kbps
Data Transmission	
Error Detection	32 Bit CRC, retransmit on error
Data Encryption	128-bit AES, Proprietary Spread Spectrum Technology
Authentication	Central Authentication and RADIUS compliant
Protocol	Ethernet 802.3, ARP, DHCP, IP, Multicast, ICMP, TCP, UDP, TFTP, FTP
Data Rate* (over the air)	867 Kbps/614 Kbps
Management	HTTP, HTTPS, Locale Console; IP Auto Discover

**OPTIONAL EMBEDDED GPS** Contact Intuicom for configurations and specifications

\* Measured assuming 75% frequency availability  
Note: Specifications subject to change without notice.

INTUICOM RADIOS REQUIRE PROFESSIONAL INSTALLATION